

MATERIAL SAFETY DATA SHEET

PRODUCT NAME: FLO PAINT FLAT CLEAR/COLORS
PRODUCT CODE: DUX450

HMS CODES: H F R P
1 0 0 B

===== SECTION I - MANUFACTURER IDENTIFICATION =====

MANUFACTURER'S NAME: LANDZETTEL & SONS
ADDRESS: 17-12 RIVER ROAD, FAIR LAWN, NEW JERSEY 07410
EMERGENCY PHONE: (201) 796-3500 INFORMATION PHONE: (201) 796-3500
DATE REVISED : 07-05-06 NAME OF PREPARER : WJL
REASON REVISED : INITIAL

===== SECTION II - HAZARDOUS INGREDIENTS/SARA III INFORMATION =====

HAZARDOUS COMPONENTS	CAS NUMBER	OCCUPATIONAL EXPOSURE LIMITS			VAPOR PRESSURE WEIGHT	
		OSHA PEL	ACGIH TLV	OTHER	mm Hg @ TEMP	PERCENT

*** NO REPORTABLE QUANTITIES OF INGREDIENTS ARE PRESENT ***

*** No toxic chemical(s) subject to the reporting requirements of section 313 of Title III and of 40 CFR 372 are present. ***

===== SECTION III - PHYSICAL/CHEMICAL CHARACTERISTICS =====

BOILING POINT: 212-374 deg. F SPECIFIC GRAVITY (H2O=1): 1.4
VAPOR DENSITY: LIGHTER THAN AIR EVAPORATION RATE: SLOWER THAN ETHER
COATING V.O.C. : 0.74 LB/GL (88 G/L)
MATERIAL V.O.C.: 0.27 LB/GL (32 G/L)
SOLUBILITY IN WATER: Soluble
APPEARANCE AND ODOR: Thick, creamy liquid with no significant odor.

===== SECTION IV - FIRE AND EXPLOSION HAZARD DATA =====

FLASH POINT: >250deg F METHOD USED: N/A
FLAMMABLE LIMITS IN AIR BY VOLUME- LOWER: N/A UPPER: N/A

EXTINGUISHING MEDIA: , WATER FOG

SPECIAL FIREFIGHTING PROCEDURES

Water may be used to cool closed containers to prevent pressure buildup and explosion when exposed to extreme heat.

UNUSUAL FIRE AND EXPLOSION HAZARDS

Closed containers may explode when exposed to extreme heat.
This product will not burn, but may spatter if the temperature exceeds the boiling point.

===== SECTION V - REACTIVITY DATA =====

**STABILITY: STABLE
CONDITIONS TO AVOID**

Coagulation may occur following freezing, thawing or boiling.

INCOMPATIBILITY (MATERIALS TO AVOID)

None reasonably foreseeable.

HAZARDOUS DECOMPOSITION OR BYPRODUCTS

N/A

HAZARDOUS POLYMERIZATION: WILL NOT OCCUR

===== SECTION VI - HEALTH HAZARD DATA =====

INHALATION HEALTH RISKS AND SYMPTOMS OF EXPOSURE

Acute overexposure in mist form may result in irritation of throat and lungs.

SKIN AND EYE CONTACT HEALTH RISKS AND SYMPTOMS OF EXPOSURE

Direct skin contact may cause skin irritation and dermatitis. May cause burning and irritation upon direct contact to the eyes.

SKIN ABSORPTION HEALTH RISKS AND SYMPTOMS OF EXPOSURE

Direct skin contact may cause skin irritation and dermatitis.

INGESTION HEALTH RISKS AND SYMPTOMS OF EXPOSURE

Severe oral intoxication will lead to intense burning of the throat and may result in drowsiness, numbness and headache followed by weakness and nausea.

HEALTH HAZARDS (ACUTE AND CHRONIC)

No short term (acute) health hazards are currently known to exist.

No long term (chronic) health hazards are currently known to exist.

•CARCINOGENICITY: NTP? NO IARC MONOGRAPHS? NO OSHA REGULATED? NO

No chemicals currently listed as carcinogens are present.

MEDICAL CONDITIONS GENERALLY AGGRAVATED BY EXPOSURE

High concentration exposure may provoke asthmatic response in persons with asthma who are sensitive to airway irritants.

EMERGENCY AND FIRST AID PROCEDURES

INHALATION: Remove to fresh air.

EYES: Promptly wash eyes with plenty of water for at least 15 minutes and consult physician if irritation persists.

SKIN: Remove with soap and water. Remove contaminated clothing.

INGESTION: Drink 1 or 2 glasses of water to dilute. Do not induce vomiting. Consult a physician or poison control center immediately.

=====
SECTION VII - PRECAUTIONS FOR SAFE HANDLING AND USE
=====**STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED**

If material is released or spilled, dam up to limit spread. Mop up or absorb on inert material and place in containers. Provide adequate ventilation to affected area and use protective equipment as specified in other sections of MSDS.

WASTE DISPOSAL METHOD

Disposal should be done in accordance with federal, state, and local regulations for non-hazardous materials.

NOTE: Spilled paint is very slippery. Use caution!

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORING

Keep container closure tight and in an upright position to prevent leakage.

Container closure should be kept tight to prevent air from entering container which could cause spoilage of the paint.

OTHER PRECAUTIONS

Do not store above 100 deg. Fahrenheit.

Store containers out of the direct sun to avoid internal buildup of pressure.

Avoid breathing sanding dust.

Do not handle until the manufacturers safety precautions have been read and understood.

=====
SECTION VIII - CONTROL MEASURES
=====**RESPIRATORY PROTECTION**

In areas with unrestricted or limited ventilation approved mechanical filter respirators to remove solid airborne particles of overspray should be used during spray application. In confined areas an approved chemical/mechanical filter respirator designed to remove both particles and vapor should be used during spray application.

VENTILATION

Use mechanical local exhaust in area of use.

PROTECTIVE GLOVES

Chemical resistant rubber or plastic preferred if prolonged contact is anticipated.

EYE PROTECTION

Safety eyewear is recommended.

OTHER PROTECTIVE CLOTHING OR EQUIPMENT

Impermeable apron is recommended to keep material off clothing.

WORK/HYGIENIC PRACTICES

Wash hands before eating or using the restroom.

=====
SECTION IX - DISCLAIMER
=====**DISCLAIMER**

The information in this MSDS was obtained from sources which we believe are reliable. However, the information is provided without any representation or warranty, express or implied, regarding its accuracy or correctness.